Sixty-second Legislative Assembly of North Dakota

HOUSE BILL NO. 1442

Introduced by

Representatives Ruby, Gruchalla

1 A BILL for an Act to amend and reenact section 39-21-45.1 of the North Dakota Century Code,

2 relating to modification of motor vehicles; and to provide for a legislative management study.

3 BE IT ENACTED BY THE LEGISLATIVE ASSEMBLY OF NORTH DAKOTA:

4 SECTION 1. AMENDMENT. Section 39-21-45.1 of the North Dakota Century Code is

5 amended and reenacted as follows:

6 **39-21-45.1. Modification of motor vehicle.**

- 1. Except as otherwise provided in this section, a person may not operate upon a public
 highway a motor vehicle of a type required to be registered under the laws of this state
 with a registered gross weight of sevensixteen thousand pounds [3175.147257.48]
 kilograms] or less with alterations or changes from the manufacturer's original design
 of the suspension, steering, or braking system of the motor vehicle. The weight mustbe computed on the basis of the unmodified and unloaded weight of the motor vehicleand without regard to any ballast that may be placed in the vehicle.
- <u>An inspection certificate from the department or highway patrol is required after the</u>
 <u>completion of all modifications before the motor vehicle with vehicle modifications from</u>
 <u>the manufacturer's original design of the suspension, steering, or braking systems</u>
 <u>may be registered.</u>
- 18 <u>3.</u> As to bumpers, motor vehicle height, <u>tires</u>, and permitted modifications<u>fenders</u>, the
 following requirements also apply:
- 20 <u>1.</u> <u>a.</u> The motor vehicle must be equipped with front and rear bumpers.
- 2. <u>b.</u> The maximum body height permitted for the motor vehicle is forty-two inches
 [106.68 centimeters]. Measurement of body height is made from a level ground
 surface to the floor of the cargo area. <u>Air or hydraulic suspension systems used</u>
 to change body height may not be actuated while the vehicle is in motion. The

Sixty-second Legislative Assembly

	, U				
1			<u>veh</u>	icle body must maintain a generally level stance and body and bumper	
2			<u>heię</u>	ants referred to in this subsection must be maintained while the vehicle is in	
3			motion.		
4	3.	<u>C.</u>	The	e maximum bumper height permitted is twenty-seven inches [68.58	
5			cen	timeters]. Measurement of bumper height is made from a level ground	
6			surf	ace to the highest point on the bottom of the bumper.	
7	4.	<u>d.</u>	The vehicle may be modified in accordance with the following:		
8		a.	(1)	Any modifying equipment must meet specialty equipment marketing	
9				associationnational highway traffic safety administration standards-or-	
10				federal motor vehicle safety standards.	
11		b.	<u>(2)</u>	If tires placed on a motor vehicle have a diameter greater than that of the	
12				tires on the motor vehicle as manufactured, those tires must comply with	
13				department of transportation requirements federal motor vehicle safety	
14				standards.	
15		C.	<u>(3)</u>	The maximum outside diameter permitted for tires is forty-four inches	
16				[111.76 centimeters].	
17		d.	<u>(4)</u>	A horizontal drop bumper may be used to comply with the bumper height	
18				requirement of subsection 3. The horizontal bumper must:	
19			(1)	Be be at least three inches [7.62 centimeters] in vertical width;	
20	1		(2)	Extend extend the entire horizontal body width; and	
21			(3)	Be be horizontal, load bearing, and attached to the vehicle framestructure to	
22				effectively transfer impact when engaged.	
23		e.	<u>(5)</u>	The maximum lift permitted in the suspension system is four inches [10.16	
24	1			centimeters].	
25		<u>e.</u>	<u>A pa</u>	art of a motor vehicle must not extend below the lowest part of a wheel rim	
26			exc	ept tires and electric grounding devices designed for that purpose.	
27		<u><u>f.</u></u>	<u>All v</u>	wheels and tires must be equipped with fenders designed to cover the entire	
28			trea	d width. Tread width is the portion of the tire that generally makes contact	
29		with the road surface. Fenders must cover the entire tread circumference from at			
30			leas	st fifteen degrees in front, to at least seventy-five degrees to the rear,	
31			mea	asured from the vertical centerline at each wheel.	

Sixty-second Legislative Assembly

1	5. g. e.	A person charged with violating this section has the burden of proceeding to			
2		show that the modifications are permitted under this section.			
3	6. <u>h.f.</u>	Vehicles owned by law enforcement agencies, the military, firefighting agencies,			
4		and ambulances may be modified without regard to this section.			
5	7.<u>4.</u>3. The	director may adopt rules to implement this section.			
6	SECTION	N 2. LEGISLATIVE MANAGEMENT STUDY - DRIVERS AND MOTOR			
7	VEHICLES.	During the 2011-12 interim, the legislative management shall consider studying the			
8	regulations of drivers and of motor vehicles in the North Dakota Century Code for consistency,				
9	clarity, and substance. The legislative management shall report its findings and				
10	recommendations, together with any legislation required to implement the recommendations, to				
11	the sixty-third legislative assembly.				