FIRST ENGROSSMENT

Sixty-fourth Legislative Assembly of North Dakota

ENGROSSED SENATE BILL NO. 2166

Introduced by

Senators Oehlke, Armstrong

- 1 A BILL for an Act to amend and reenact section 39-21-45.1 of the North Dakota Century Code,
- 2 relating to modified vehicles.

3 BE IT ENACTED BY THE LEGISLATIVE ASSEMBLY OF NORTH DAKOTA:

4 SECTION 1. AMENDMENT. Section 39-21-45.1 of the North Dakota Century Code is

5 amended and reenacted as follows:

6 **39-21-45.1. Modification of motor vehicle.**

- Except as otherwise provided in this section, a personan individual may not operate
 upon a public highway a motor vehicle of a type required to be registered under the
- 9 laws of this state with a weight of seventen thousand pounds [3175.144535.92]
- 10 kilograms] or less with alterations or changes from the manufacturer's original design
- of the suspension, steering, or braking system of the motor vehicle. The weight must
 be computed on the basis of the unmodified and unloaded weight of the motor vehicle
- 13 and without regard to any ballast that may be placed in the vehicle.
- As to bumpers, motor vehicle height, and permitted modifications, the following
 requirements also apply:
- 16 <u>1.</u> <u>a.</u> The motor vehicle must be equipped with front and rear bumpers.
- 17 2. b. The maximum body height permitted for the motor vehicle is forty-two inches
 18 [106.68 centimeters]. Measurement of body height is made from a level ground
 19 surface to the floor of the cargo area.
- 203.c.The maximum bumper height permitted is twenty-seven inches [68.5821centimeters]. Measurement of bumper height is made from a level ground22surface to the highest point on the bottom of the bumper.
- 23 4. <u>d.</u> The vehicle may be modified in accordance with the following:

Sixty-fourth Legislative Assembly

1		a.	(1)	Any modifying equipment must meet specialty equipment marketing-
2				association standardsthe director's requirements.
3		b.	<u>(2)</u>	If tires placed on a motor vehicle have a diameter greater than that of the
4				tires on the motor vehicle as manufactured, those tires must comply with
5				department of transportationthe director's requirements.
6		C.	<u>(3)</u>	The maximum outside diameter permitted for tires is forty-four inches
7				[111.76 centimeters].
8		d.	<u>(4)</u>	A horizontal drop bumper may be used to comply with the bumper height
9				requirement of subsection 3. The horizontal bumper must:
10			(1)	Bebe at least three inches [7.62 centimeters] in vertical width;
11			(2)	Extendextend the entire horizontal body width; and
12			(3)	Bebe horizontal, load bearing, and attached to the vehicle frame to
13				effectively transfer impact when engaged.
14		e.	<u>(5)</u>	The maximum lift permitted in the suspension system is four inches [10.16
15				centimeters].
16	5.	<u>e.</u>	A pe	ersonAn individual charged with violating this section has the burden of
17			proc	ceeding to showshowing that the modifications are permitted under this
18			sect	tion.
19	6.	<u>f.</u>	Vehicles owned by law enforcement agencies, the military, firefighting agencies,	
20			and	ambulances may be modified without regard to this section.
21	7.	<u>g.</u>	The	director may adopt rules to implement this section.